



# POWER-V DXT

**APPLICATIONS:** 4X4s, 3/4 TO 1-TON TRUCKS AND SUVs, MEDIUM-DUTY TRUCKS 14,000-27,000 GVWR (10' ONLY)



SPECIFICATIONS	8'2" Power-V DXT (Steel   Poly   Stainless)	9'2" Power-V DXT (Steel   Poly   Stainless)	10' Power-V DXT (Steel)
Blade Width (Straight)	98" (249 cm)	110" (279 cm)	120" (305 cm)
Blade Width (Vee)	88" (224 cm)	99" (251 cm)	107" (272 cm)
Blade Width (Scoop)	81" (206 cm)	92" (234 cm)	102" (259 cm)
Plowing Width @ 30° Angle	85" (216 cm)	95" (241 cm)	104" (264 cm)
Blade Height	30" (76 cm) at center, 37-1/2" (95 cm) at end	30" (76 cm) at center, 37-1/2" (95 cm) at end	35" (88 cm) at center, 45" (114 cm) at end
Blade Thickness	11-ga steel   3/8" Poly   12-ga 304 Stainless Steel	11-ga steel   3/8" Poly   12-ga 304 Stainless Steel	11-ga Steel
Base Angle	*1/2" x 6" (1.3 cm x 15 cm)	*1/2" x 6" (1.3 cm x 15 cm)	*1/2" x 6" (1.3 cm x 15 cm)
Reinforcement Ribs	6 vertical, 2 diagonal	8 vertical, 2 diagonal	8 vertical, 2 diagonal
Plow Shoes	Optional	Optional	Optional
Trip Springs (Moldboard)	4 Extension Springs	4 Extension Springs	4 Extension Springs
Trip Springs (Cutting Edge)	3 Torsion Springs (per blade half)	3 Torsion Springs (per blade half)	3 Torsion Springs (per blade half)
Angle Cylinders	1-1/2" x 10" (4 cm x 25 cm)	1-1/2" x 10" (4 cm x 25 cm)	2" x 10" (5.08 cm x 25.4 cm)
Lift Cylinder	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2-1/4" x 1-1/8" x 12" (5.72 cm x 2.86 cm x 30.48 cm)
Attachment System	SmartHitch 2	SmartHitch 2	SmartHitch 2
Plow Weight*	868 lb (394 kg)   878 lb (388 kg)   920 lb (417 kg)	925 lb (420 kg)   935 lb (424 kg)   977 lb (433 kg)	1205 lb (546.58 kg)
Plow Lights	SmartLight 2 (SL3 L.E.D. Optional)	SmartLight 2 (SL3 L.E.D. Optional)	SmartLight 2 (SL3 L.E.D. Optional)

\*Plow weight does not include vehicle mount weight. Vehicle mount weight range: 130-160 lb (59-73 kg).

Patented Dual Trip Design. 9,051,700.

\*\*The tripping base angles on the DXT come standard with curb guards and snow catcher, and can be used as the cutting edge until worn. The optional cutting edge is made from HARDOX® for maximum wear resistance and durability.

**TWO-YEAR LIMITED WARRANTY** - All BOSS Snowplows and equipment are guaranteed to be free from defects in material and workmanship for two full years from the date of purchase. Stop by any Authorized BOSS dealer to receive complete details on our Two-year parts and labor warranty.

**LEGAL STATEMENT** - Vehicles intended to be equipped with a spreader and/or snowplow must comply with the vehicle manufacturers' specifications for equipment application. BOSS Products/Northern Star Industries, Inc. reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications use herein.

BOSS Products are covered under one or more of the following patent numbers: U.S. Patents: 4,074,448; 4,658,519; 5,568,694; 6,170,178; 6,134,814; 6,108,946; 6,467,199; 7,437,839; 8,793,907; 8,978,276; 9,051,700. Canadian Patents: 1,300,877; 2,330,135. Other patents pending. ©2015 BOSS Products/The Toro Company. All rights reserved.